



## THE NEW BENCHMARK IN TOUGHNESS & LOW MAINTENANCE



**7' Wide**

If you've got a job to do, the new Haulmark ALX is the way to do it. All-Aluminum construction results in a lighter trailer for increased fuel economy and increased hauling capacity. And, the Haulmark ALX won't rust even on the saltiest roads, so your trailer will keep looking great job-after-job, year-after-year. The Haulmark ALX features a tube perimeter frame and fully integrated sidewall and roof design that delivers commercial grade durability. Be sure to check out the innovative "Overlock" roof design — an

industry first. This pioneering design provides superior weathertightness that is both screwless and seamless. Beauty and brawn in one easy to tow lightweight package!



6' Wide Model shown above. Your choice of Rear Ramp Door or Double Rear Doors — STANDARD!

**Haulmark®**

**GET MORE | GO FURTHER**

[www.haulmark.com](http://www.haulmark.com)

# ALX ALUMINUM UTILITY TRAILERS

		HAUV6X12DS	HAUV7X14WT2	HAUV7X16WT2	HAUV85X16WT2*	HAUV85X20WT2*	HAUV85X24WT3
<b>Body:</b>	<b>Length (Incl. "V")</b>	13'11"	16'2"	18'2"	18'8"	22'8"	26'8"
	<b>Width</b>	6'0"	6'9"	6'9"	8'5"	8'5"	8'5"
<b>Overall:</b>	<b>Length</b>	16'4"	18'10"	21'1"	21'3"	25'3"	29'3"
	<b>Width</b>	7'9"	8'6"	8'6"	8'6"	8'6"	8'6"
	<b>Height</b>	8'0"	8'3"	8'3"	8'4"	8'4"	8'6"
<b>Interior:</b>	<b>Length</b>	13'7"	15'10"	17'10"	18'4"	22'4"	26'4"
	<b>Width</b>	5'9"	6'6"	6'6"	8'2"	8'2"	8'2"
	<b>Height</b>	6'6"	6'6"	6'6"	6'6"	6'6"	6'6"
<b>Platform Height:</b>		19"	19"	19"	20"	20"	22"
<b>Axle:</b>	<b>Quantity</b>	Single	Tandem	Tandem	Tandem	Tandem	Tandem
	<b>Capacity</b>	3500 lbs.	7000 lbs.	7000 lbs.	7000 lbs.	7000 lbs.	10,000 lbs.
	<b>Type</b>	10° Up	10° Up	10° Up	10° Up	10° Up	10° Up
	<b>Suspension</b>	Dexter Torflex®	Dexter Torflex®	Dexter Torflex®	Dexter Torflex®	Dexter Torflex®	Dexter Torflex®
	<b>Brakes</b>	OPT	STD	STD	STD	STD	STD
<b>Tires:</b>	<b>Size</b>	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST225/75R16
	<b>Load Range</b>	C	C	C	C	C	D
	<b>Type</b>	Radial	Radial	Radial	Radial	Radial	Radial
<b>Hitch:</b>	<b>Ball Size</b>	2"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
	<b>To Top of Ball</b>	16"	16"	16"	18"	18"	20"
<b>GVWR:</b>		2990 lbs.	7000 lbs.	7000 lbs.	7000 lbs.	7000 lbs.	10,000 lbs.
<b>Rear Door: Width x Height</b>		64" x 74"	73" x 74"	73" x 74"	93" x 74"	93" x 74"	93" x 74"
<b>Side Door: Width</b>		32"	32"	32"	36"	36"	36"
<b>Tube Main Rails:</b>		2" x 4"	2" x 4"	2" x 4"	2" x 6"	2" x 6"	2" x 6"
<b>12V End Connector:</b>		4-way	7-way	7-way	7-way	7-way	7-way

\*Also available in a 10,000# GVWR.

## Features | Benefits

- All-Aluminum Hardware
- Aluminum Tube Perimeter Frame
- 24" OC Floor Crossmembers
- 16" OC Wall Posts
- 24" OC Roof Framing
- V-Nose Front
- Dexter Torflex Axles with EZ-Lube Hubs
- Silver Aluminum Wheels
- 3/4" DryMax® High-Performance Decking
- 3/8" DryMax® High-Performance Wall Liner
- ABS Sidewall Vents
- LED 12V Interior Lighting with Switch (Made in the USA)
- .030 Bonded (Screwless) Exterior
- Thick, Bold Extruded Aluminum Top/Bottom Trim
- Innovative "Overlock" Aluminum Roof Design is Screwless and Seamless
- Aluminum Framed Side Door with Flush Lock
- Choice of Standard Ramp or Double Rear Doors
- 24" ATP Stoneguard
- LED Exterior Lighting Tail/Clearance (Made in the USA)
- 6-Year Limited Warranty



Fully Integrated, All Tube, Roof and Sidewall Design for Maximum Strength



**GET MORE | GO FURTHER**

[www.haulmark.com](http://www.haulmark.com)

Specifications, features & available options subject to change without notice.  
©Haulmark 2015 Form: HM\_ALXUT\_SPEC (5.6.2015)