





The Official Trailer of the Active Family



The **FLEX** from Haulmark is a stylish, versatile and smart solution to your light cargo hauling needs. The top flips open. The ramp folds down. Pop a couple of clamps to detach the roof altogether. The **FLEX**'s lightweight all aluminum frame and low-profile design deliver carefree towing behind the smallest of tow vehicles. Chances are if it has a hitch, it can pull a **FLEX**. When you return back home, your **FLEX** fits neatly in the garage ready for the next family chore. Whoever said, "You can't take it with you," didn't own a **FLEX**!





Your Haulmark **FLEX** "to do" list:

- **☑** Bicycle Tours
- **☑**Tailgate Parties
- **☑** Beach Vacations
- **■** Landscape Supplies
- **☑** College Move-In Day
- **™**Camping Adventures
- **☞**Antique Shopping Trips
- **™**Holiday Luggage Hauler
- **■** Appliance & Furniture Moving



GET MORE | GO FURTHER

MODEL SPECIFICATIONS

MODEL	FL4X6DS0	FL5X8DS1	FL5X8DS1	FL5X8DS1
Additional Height	None	None	+6"	+12"
Body: Length	6'0"	8'6"	8'6"	8′6″
Width	4'0"	5′0″	5′0″	5′0″
Overall: Length	9'8"	12′6″	12'6"	12'6"
Width (includes fenders)	5′5″	6'9"	6'9"	6'9"
Height	4′0″	4'10"	5'4"	5′10″
Interior: Length	5′8″	8'2"	8′2″	8′2″
Width	3'10"	4'10"	4'10"	4'10"
Height	2'6"	3'4"	3'10"	4'4"
Platform Height	15"	16"	16"	16"
Axles	Single	Single	Single	Single
Axle Type	22-1/2° Up Angle	10° Up Angle	10° Up Angle	10° Up Angle
Suspension	Torflex*	Torflex*	Torflex*	Torflex*
Tire Size	13"	13"	13"	13"
Load Range	С	C	С	C
Wheel Bolt Pattern	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5
Hitch Ball Size	2"	2"	2"	2"
Hitch Height (to top of ball)	15"	16"	16"	16"
Hitch Weight (% of curb weight)	10-15%	10-15%	10-15%	10-15%
Swing-Away Tongue Jack	No	Yes	Yes	Yes
Curb Weight (lb.)	410	685	725	745
GAWR (lb.)	1100	2500	2500	2500
Payload Capacity (lb.)	590	1815	1775	1755
Cubic Capacity (cubic ft.)	54	131	151	171
Rear Door Style	Swing	Ramp	Ramp	Ramp
Rear Door Opening: Width	40"	52"	52"	52"
Height	24"	33"	39"	45"







©Haulmark 2010 LITHO USA Form FLEX0510R1115

STANDARD FEATURES:

- Aluminum Frame
- Torflex® Rubber Torsion Axles with EZ Lube Hubs

Specifications and features subject to change without notice.

- 13" Radial Tires & 5-Bolt Silver Spoke Wheels
- · Smooth Aluminum Fenders
- · 3/4"Treated Plywood Decking
- · Laminated Aluminum Sidewall Panels
- Removable One-Piece High Impact, Thermo-Polymer Roof with Convenient Tip-Up Function
- Keyed Compression Locks
- LED Exterior Lighting with Safety Package
- 12 Volt Trailer End Connector (4-way plug)
- 2" Ball Coupler
- One-Piece Removable Drawbar with Lifting Handle
- · Safety Chains with Hooks





*Photos above and on front cover feature <u>optional</u> Side Graphics and Interior Spare Tire Carrier w/ Spare Tire.

Proud Member of

