



SPECIFICATIONS



	VTM8522T2	VTM8522T3	VTM8528T3
Body: Length Width	22' 0" 8' 4"	22' 0" 8' 4"	28′0″ 8′ 4″
Length Overall: Width Height	24' 9" 8' 6" 9'1"	24'9" 8' 6" 9'1"	30′9″ 8′ 6" 9′1″
Length (including "V") nterior: Width Height	21' 8" 8' 1" 7'0"	21' 8" 8' 1" 7'0"	27' 8" 8' 1" 7'0"
Width Between Wheel Boxes	78-1/2"	78-1/2"	78-1/2"
Platform Height	19"	19"	19"
Torflex® Suspension E-Z® Lube Axles: Q Tyj		Tandem 45° Down	Tandem 45° Down
Electric Brakes with Breakaway Kit	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size Fire Load Range	ST205/75R15 C	ST225/75R15 D	ST225/75R15 D
Hitch Ball Size	25/16"	25/16"	25/16″
Hitch Height to Top of Ball	18"	18"	18"
Hitch Weight (% of Curb Weight)	10% to 15%	10% to 15%	10% to 15%
GVWR	7,000 lbs.	9,990 lbs.	9,990 lbs.
Curb Weight <i>(Approximate)</i>	3,140 lbs.	3,190 lbs.	3,890 lbs.
Payload Capacity (<i>Approximate</i>)	3,860 lbs.	6,800 lbs.	6,100 lbs.
Flush Lock Side Door Width	36"	36"	36"
Front Ramp Door Opening - Width x Height	66" x 78"	66" x 78"	66" x 78"
Rear Ramp Door Opening - Width x Height	94" x 82"	94" x 82"	94" x 82"
Beavertail Length	48"	48"	48"
12v Male Connection	7-way	7-way	7-way

STANDARD FEATURES

- 6'V-Front with Polished Aluminum Front Nose
- · Mid-Deck Platform with Drive Over Wheel Boxes
- Rear Ramp Door with 12" Premium Aluminum Ramp Extension
- Front Ramp Door
- 36" Side Entry Door with Fold Down Step (Road Side)
- All-Aluminum Hardware
- Aluminum Tube Perimeter Frame
- Fully Integrated, All Tube, Roof and Sidewall Design
 - 16" OC Tube Floor Crossmembers
 - 16" OC Tube Wall Posts
 - 16" OC Tube Roof Framing
- 3-Piece A-Frame with 2000 lb. Front Wind Tongue Jack
- Aluminum Fenderettes
- Torflex® Torsion Axles
- Radial Tires with Silver Viper Aluminum Wheels
- 3/4" PlexCore™ High-Performance Flooring
- · White Vinyl Interior Sidewall Liner
- ATP Kickplate (12"H)
- 12v LED Interior Dome Lights (2) with Switch
- 12v LED Exterior Lighting Tail/Clearance Lights
- · LED Rear ID Bar with Loading Light
- 1-Piece Aluminum Roof
- Bonded (Screwless) .030 Aluminum Exterior
- Non-Powered Roof Vent
- Flow-Thru Sidewall Vents
- 5,000 lb. D-Rings
- 24" ATP Stoneguard
- 14" x 14" Access Door
- Aluminum Fold-Down Step
- 3 Year Limited Warranty





Trailers shown may feature optional equipment available at an additional charge.



