





SPECIFICATIONS



		VTMS8522T2	VTMS8522T3	VTMS8528T3	VTMS8530T3
Body:	Length Width	22' 0" 8' 4"	22' 0" 8' 4"	28′0″ 8′4"	30′0″ 8′4″
verall:	Length Width Height	24' 9" 8' 6" 9' 2"	24'9" 8' 6" 9' 2"	30' 9" 8' 6" 9' 2"	32′9″ 8′ 6″ 9′ 2″
nterior:	Length (including "V") Width Height	21' 8" 8' 1" 7' 0"	21' 8" 8' 1" 7' 0"	27' 8" 8' 1" 7' 0"	29' 8" 8' 1" 7' 0"
Width Between Wheel Boxes		83"	83"	83"	83"
Platform Height		21"	21"	21"	21"
orflex® Su	spension E-Z® Lube Axles: Qty Type	Tandem 45° Down	Tandem 45° Down	Tandem 45° Down	Tandem 45° Down
lectric Bral	kes with Breakaway Kit	Electric Drum	Electric Drum	Electric Drum	Electric Drum
adial Tire S ire Load Ra		ST205/75R15 C	ST225/75R15 D	ST225/75R15 D	ST225/75R15 D
litch Ball Si	ize	25/16"	25/16"	25/16"	25/16"
Hitch Height to Top of Ball		23"	23"	23"	23"
Hitch Weight (% of Curb Weight)		10% to 15%	10% to 15%	10% to 15%	10% to 15%
GVWR		7,000 lb.	9,990 lb.	9,990 lb.	9,990 lb.
Curb Weight (<i>Approximate</i>)		3,320 lb.	3.420 lb.	4,230 lb.	4,530 lb.
Payload Capacity (Approximate)		3,680 lb.	6,570 lb.	5,760 lb.	5,460 lb.
Flush Lock Side Door Width - Width x Height		36" x 78"	36" x 78"	36" x 78"	36" x 78"
Front Ramp Door Opening - Width x Height		66" x 78"	66" x 78"	66" x 78"	66" x 78"
Rear Ramp Door Opening - Width x Height		94" x 80"	94" x 80"	94" x 80"	94" x 80"
Beavertail Length		48"	48"	48"	48"
12v Male Connection		7-way	7-way	7-way	7-way

STANDARD FEATURES

- 6'V-Front with Polished Aluminum Front Nose
- Mid-Deck Platform with Tapered Drive Over Wheel Boxes
- 94"W Rear Ramp Door
- 12" Premium Aluminum Ramp Extension
- 66"W Front Ramp Door
- 36" Side Entry Door with Fold Down Steel Step (Road Side)
- 16" OC Floor Crossmembers
- 16" OC Tube Vertical Wall Posts
- 16" OC Tube Roof Framing
- 2000 lb. Front Wind Tongue Jack
- · Smooth Aluminum Fenderettes
- Torflex® Torsion Axles
- Radial Tires with Aluminum Wheels
- 3/4" PlexCore™ High-Performance Flooring
- White Vinyl Interior Sidewall Liner
- ATP Kickplate (12"H)
- 12v LED Interior Dome Lights (2) with Switch
- 12v LED Exterior Lighting Tail/Clearance Lights
- LED Rear ID Bar with Loading Light with Switch
- 1-Piece Aluminum Roof
- Bonded (Screwless) .030 Aluminum Exterior
- Flow-Thru Sidewall Vents
- 14in x 14in Non-Powered Roof Vent
- 5,000 lb. D-Rings (6)
- 24" ATP Stoneguard
- 14" x 14" Access/Fuel Door
- 3-Year Limited Warranty





Trailers shown may feature optional equipment available at an additional charge.



