

Haulmark®

THE BENCHMARK IN TOUGHNESS & LOW MAINTENANCE

If you've got a job to do, the Haulmark® ALX Utility is the way to do it. All-aluminum construction results in a lighter trailer for increased fuel economy and increased hauling capacity. The Haulmark® ALX Utility won't rust even on the saltiest roads, so your trailer will keep looking great job after job, year after year. Beauty and brawn in one easy-to-tow, lightweight package!



Trailers shown may feature optional equipment available at an additional charge.

ALL ALUMINUM

Haulmark® ALX

SPECIFICATIONS

ALL ALUMINUM
Haulmark® ALX

	HAUV6X12DS	HAUV7X14WT2	HAUV7X16WT2	HAUV85X16WT2*	HAUV85X20WT2*	HAUV85X24WT3
Body: Length (Including "V") Width	13' 11" 6' 0"	16' 2" 6' 9"	18' 2" 6' 9"	18' 8" 8' 5"	22' 8" 8' 5"	26' 8" 8' 5"
Overall: Length Width Height	16' 4" 7' 9" 8' 2"	18' 10" 8' 6" 8' 3"	21' 1" 8' 6" 8' 3"	21' 3" 8' 6" 8' 4"	25' 3" 8' 6" 8' 4"	29' 3" 8' 6" 8' 6"
Interior: Length Width Height	13' 7" 5' 9" 6' 6"	15' 10" 6' 6" 6' 6"	17' 10" 6' 6" 6' 6"	18' 4" 6' 6" 6' 6"	22' 4" 8' 2" 6' 6"	26' 4" 8' 2" 6' 6"
Platform Height	19"	19"	19"	20"	20"	22"
Torflex® Suspension E-Z Lube® Axles: Qty Total Axle Capacity Type	Single 3,500 lbs. 10° Up	Tandem 7,000 lbs. 10° Up	Tandem 7,000 lbs. 10° Up	Tandem 7,000 lbs. 10° Up	Tandem 7,000 lbs. 10° Up	Tandem 10,000 lbs. 10° Up
Electric Brakes with Breakaway Kit	Optional	Electric Drum	Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size Tire Load Range	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST225/75R16 D
Hitch Ball Size	2"	2½"	2½"	2½"	2½"	2½"
Hitch Height to Top of Ball	16"	16"	16"	18"	18"	20"
Hitch Weight (% of Curb Weight)	10% - 15%	10% - 15%	10% - 15%	10% - 15%	10% - 15%	10% - 15%
GVWR	2,990 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.	10,000 lbs.
Curb Weight (Approximate)	1,475 lbs.	2,000 lbs.	2,200 lbs.	2,600 lbs.	3,000 lbs.	3,425 lbs.
Payload Capacity (Approximate)	1,515 lbs.	5,000 lbs.	4,800 lbs.	4,400 lbs.	4,000 lbs.	6,575 lbs.
Rear Door Opening - Width x Height	64" x 74"	73" x 74"	73" x 74"	93" x 74"	93" x 74"	93" x 74"
Side Door Width	32"	32"	32"	36"	36"	36"
Tube Main Rails	2" x 4"	2" x 4"	2" x 4"	2" x 6"	2" x 6"	2" x 6"
12v Male Connection	4-Way	7-Way	7-Way	7-Way	7-Way	7-Way

STANDARD FEATURES

- All-Aluminum Hardware
- Aluminum Tube Perimeter Frame
- 24" OC Floor Crossmembers
- 16" OC Wall Posts
- 24" OC Roof Framing
- V-Nose Front
- Dexter® Torflex® Axles with EZ-Lube® Hubs
- Silver Aluminum Wheels
- 3/4" PlexCore™ High-Performance Floor & Ramp Decking
- 3/8" PlexCore™ High-Performance Wall Liner
- ABS Sidewall Vents
- 12v LED Interior Lighting with Switch (Made in the USA)
- .030 Bonded (Screwless) Exterior
- Thick, Bold Extruded Aluminum Top/Bottom Trim
- 1-Piece Aluminum Roof
- Aluminum Framed Side Door with Flush Lock
- Choice of Standard Ramp or Double Rear Doors
- 24" ATP Stoneguard
- 12v LED Slim Line Tail Lights
- 12v LED Clearance Lights
- 6-Year Limited Warranty



Trailers shown may feature optional equipment available at an additional charge.



GET MORE | GO FURTHER

www.haulmark.com

Specifications, features, options, packages & pricing subject to change **without** notice. See your authorized Haulmark® dealer for more information.