

EDGE® ALX RACE TRAILERS

Haulmark®

**WHEN SECOND
BEST ISN'T
GOOD ENOUGH!**

You love your car . . . the best engine, the best tires, the best brakes. Haulmark® has an all-aluminum race trailer that lives up to your exacting standards.

The EDGE® ALX!



Trailers shown may feature optional equipment available at an additional charge.

THE EDGE® ALX
ALL ALUMINUM

SPECIFICATIONS



	EGALX8520T3	EGALX8524T3	EGALX8528T4	EGALX8532R4
Body:	Length 20' 0"	Length 24' 0"	Length 28' 0"	Length 32' 0"
	Width 8' 4"	Width 8' 4"	Width 8' 4"	Width 8' 4"
Overall:	Length 24' 6"	Length 28' 6"	Length 32' 6"	Length 36' 6"
	Width 8' 6"	Width 8' 6"	Width 8' 6"	Width 8' 6"
	Height 8' 8"	Height 8' 9"	Height 8' 10"	Height 8' 10"
Interior:	Length 19' 8"	Length 23' 8"	Length 27' 8"	Length 31' 8"
	Width 8' 2"	Width 8' 2"	Width 8' 2"	Width 8' 2"
	Height 6' 10"	Height 6' 10"	Height 6' 10"	Height 6' 10"
Width Between Wheel Boxes	80"	80"	80"	80"
Height of Wheel Box from Floor	10"	10"	11.25"	11.25"
Platform Height	21"	21"	22"	22"
Torflex® Suspension E-Z Lube® Axles: Qty	Tandem	Tandem	Tandem	Triple
Electric Brakes with Breakaway Kit	Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size	ST205/75R15	ST225/75R15	ST235/80R16	ST235/80R16
Tire Load Range	D	E	E	E
Hitch Ball Size	2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball	21"	21"	22"	22"
Hitch Weight (% of Curb Weight)	10% - 15%	10% - 15%	10% - 15%	10% - 15%
GVWR	9,900 lbs.	9,900 lbs.	12,000 lbs.	18,000 lbs.
Curb Weight (Approximate)	3,700 lbs.	4,200 lbs.	5,000 lbs.	6,800 lbs.
Payload Capacity (Approximate)	6,200 lbs.	5,700 lbs.	7,000 lbs.	11,200 lbs.
Rear Ramp Door Opening - Width x Height	96" x 83"	96" x 83"	96" x 83"	96" x 83"
12v Male Connection	7-way	7-way	7-way	7-way
Tube Main Rails	2" x 6"	2" x 6"	2" x 6"	2" x 6"
Beavertail	36"	48"	48"	48"

STANDARD FEATURES

- Flat Front/Flat Roof Design
- All-Aluminum Frame Construction
- Aluminum Door Holdback
- Fully Integrated, All Tube, Roof and Sidewall Design
 - 16" OC Floor Crossmembers
 - 16" OC Wall Posts
 - 16" OC Roof Framing
- .030 Aluminum Exterior Smooth Bonded
- Bright Polished Aluminum Cap and Front Corners
- Bright Polished Aluminum Rear Corners and Header
- Wide Extruded Aluminum Top and Bottom Trim
- 1- Piece Aluminum Roof
- 24" ATP Stoneguard
- Spring-Assisted Rear Ramp Door with 96" Opening
- Heavy-Duty Recessed Ramp Door Handles
- 36" Aluminum Framed Side-Entry Door with Flush Lock
- Spread Torflex® Axle Design with Aluminum Fenderettes
- Goodyear® Radial Tires with Silver Viper Wheels*
- 12v LED Clear Lens Clearance Lights
- 12v LED Clear Lens Slim Line Tail Lights
- 12v LED Dome Lights with Wall Switch (4)
- 14" x 14" Non-Powered Roof Vents (2)
- 5,000 lbs. Square D-Rings with Welded Plates (4)
- 3/4" PlexCore™ Flooring
- 3/8" PlexCore™ Sidewall Liner
- Economy Ceiling Liner
- 3-Year Limited Warranty



*Trailers feature optional equipment available at additional charge.

*Trailers equipped with 7,000 lb. axles do not have Goodyear® tires as standard equipment.



GET MORE | GO FURTHER

www.haulmark.com

Specifications, features, options, packages & pricing subject to change **without** notice. See your authorized Haulmark® dealer for more information.