

Haulmark®

WHEN RACING BECOMES MORE THAN A HOBBY

Are you ready for the big time? Then take a look at the EDGE® ALX Stacker trailers, designed for the motorsports professional and serious recreational enthusiast. Not only are EDGE® ALX Stackers large enough to haul multiple vehicles, but they have enough storage space for spare parts, tools and diagnostic equipment.



Trailers shown may feature optional equipment available at an additional charge.

THE EDGE ALX
ALL ALUMINUM

SPECIFICATIONS



		HARS85X24WR4	HARS85X24WR5	HARS85X28WR5	HARS85X32WR5
Body:	Length	24' 0"	24' 0"	28' 0"	32' 0"
	Width	8' 4"	8' 4"	8' 4"	8' 4"
Overall:	Length	29' 0"	29' 0"	33' 0"	37' 0"
	Width	8' 6"	8' 6"	8' 6"	8' 6"
	Height	13' 5"	13' 5"	13' 5"	13' 5"
Interior:	Length	23' 8"	23' 8"	27' 8"	31' 8"
	Width	8' 0"	8' 0"	8' 0"	8' 0"
	Height	11' 3"	11' 3"	11' 3"	11' 3"
Width Between Wheel Boxes		81"	81"	81"	81"
Platform Height		25"	25"	25"	25"
Auto Lift Length		13' 0"	13' 0"	16' 0"	16' 0"
Auto Lift Height		6' 8"	6' 8"	6' 8"	6' 8"
Torflex® Suspension E-Z Lube® Axles: Qty		Triple	Triple	Triple	Triple
Electric Brakes with Breakaway Kit		Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size		LT235/85R16	LT235/85R16	LT235/85R16	LT235/85R16
Tire Load Range		G	G	G	G
Hitch Ball Size		2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball		23"	23"	23"	23"
Hitch Weight (% of Curb Weight)		10% - 15%	10% - 15%	10% - 15%	10% - 15%
GVWR		18,000 lbs.	21,000 lbs.	21,000 lbs.	21,000 lbs.
Curb Weight (Approximate)		7,600 lbs.	8,750 lbs.	9,600 lbs.	10,700 lbs.
Payload Capacity (Approximate)		10,400 lbs.	12,250 lbs.	11,400 lbs.	10,300 lbs.
Rear Ramp Door Opening - Width x Height		92" x 96"	92" x 96"	92" x 96"	92" x 96"
Side Double Door Opening - Width x Height		48" x 72"	48" x 72"	60" x 78"	60" x 78"
12v Male Connection		7-way	7-way	7-way	7-way
Tube Main Rails		2" x 8"	2" x 8"	2" x 8"	2" x 8"

STANDARD FEATURES

- Polished Aluminum Front Cap & Corners
- 1-Piece Aluminum Roof
- .040 Bonded Aluminum Exterior (No Screws)
- Spread Axles with Drop Skirting
- 24" ATP Stoneguard
- 8-Bolt 16" Radial Tires with Silver Viper Aluminum Wheels
- 2-5/16" Adjustable Height Coupler (25,000 lbs.)
- 12K Hydraulic Landing Gear with Manual Override
- 12v LED 9" x 7" Exterior Scene Lights (4)
- 12v LED Clear Lens Exterior Lighting
- 3/4" PlexCore™ Decking w/ Black Coin Rubber Floor Covering
- 3/8" PlexCore™ Sidewall Liner w/ .030 White Aluminum Covering
- White Vinyl Ceiling Liner
- Steel Car Hoist System with 36" Extension
- Bunk/Attic (6' 6" from Floor to Under Side of Bunk/Attic)
- 36" Aluminum Ramp Extension with Large Bumpers
- Generator Compartment with 48" x 32" Access Door
- Air Compressor Prep Package
- 120/240v 50 amp Motorbase Receptacle with Lock Connect
- 12v Main Shut Off Switch
- 12v LED 14" Flush Mount Ceiling Lights (8)
- 12v LED 6" Round Flush Mount Dome Lights (4)
- 16" OC Tube Crossmembers
- 16" OC Vertical Posts
- 16" OC Tube Roof Structure
- Marine Battery with Vented Interior Floor Mount Box
- D-Ring Tie-Downs with Welded Plates (4)



Trailers shown may feature optional equipment available at an additional charge.



GET MORE | GO FURTHER

www.haulmark.com

Specifications, features, options, packages & pricing subject to change **without** notice. See your authorized Haulmark® dealer for more information.