

Haulmark®

YOUR PASSION IS RACING

OUR PASSION IS TRAILERS

Haulmark® understands and appreciates your passion for racing. We feel the same way about trailers. That's why we put so much heart into our EDGE® series. Heart in the form of superior engineering, head-turning style, unmatched performance, and dependability you can bank on. You need that "Edge" to be in the winner's circle - Haulmark's got it!



Trailers shown may feature optional equipment available at an additional charge.

THE EDGE®
by Haulmark

SPECIFICATIONS



	EGP8520T3	EGP8524T3	EGP8528T4	EGP8532R4
Body:				
Length	20' 0"	24' 0"	28' 0"	32' 0"
Width	8' 4"	8' 4"	8' 4"	8' 4"
Overall:				
Length	24' 7"	28' 7"	32' 7"	36' 7"
Width	8' 6"	8' 6"	8' 6"	8' 6"
Height (to top of roof vent)	9' 1"	9' 1"	9' 3"	9' 3"
Interior:				
Length	19' 8"	23' 8"	27' 8"	31' 8"
Width	8' 1"	8' 1"	8' 1"	8' 1"
Height	6' 10"	6' 10"	6' 10"	6' 10"
Width Between Wheel Boxes	83"	83"	83"	83"
Height of Wheel Box from Floor	10"	10"	10"	10"
Platform Height at Beavertail	19"	19"	21"	21"
Torflex® Suspension E-Z Lube® Axles: Qty	Tandem	Tandem	Tandem	Triple
Electric Brakes with Breakaway Kit	Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size	ST225/75R15	ST225/75R15	ST235/80R16	ST235/80R16
Tire Load Range	E	E	E	E
Hitch Ball Size	2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball	20"	20"	22"	22"
Hitch Weight (% of Curb Weight)	10% - 15%	10% - 15%	10% - 15%	10% - 15%
GVWR	9,900 lbs.	9,900 lbs.	12,000 lbs.	18,000 lbs.
Rear Ramp Door Opening - Width x Height	94" x 78"	94" x 78"	94" x 78"	94" x 78"
12v Male Connection	7-way	7-way	7-way	7-way
Tube Main Rails	2" x 6"	2" x 6"	2" x 8"	2" x 8"
Beavertail	32"	48"	72"	72"

STANDARD FEATURES

- Flat Front/Flat Roof Design
- Roof and Sidewall Structure
 - 16" OC Floor Crossmembers
 - 16" OC Tube Wall Posts
 - 16" OC Tube Roof Structure
- 54" A-Frame with Center Tube
- .030 Aluminum Exterior, Smooth Bonded
- Cast Aluminum Corners (Front & Rear)
- Stainless Steel Cap and Front Corners
- Chrome Rear Header
- 1-Piece Aluminum Roof
- ArmorTech™ on A-Frame and Rear End Rail
- 24" ATP Stoneguard
- Spring-Assisted Rear Ramp Door with 94"W Opening
- Locking Paddle Latch on Rear Ramp Door
- 36" x 78" Side Entry Door with Recessed Step
- Spread Torflex® Axle Design with Drop Skirting
- Goodyear® Radial Tires* with Black Viper Aluminum Wheels
- 12v Clear Lens LED Exterior Lighting
- 12v Clear Lens Slim Line Tail Light (2 pr.)
- 12v LED Dome Lights with Wall Switch (4)
- 14" x 14" Non-Powered Roof Vent (2)
- 5,000 lbs. Square D-Rings with Welded Plate (4)
- 3/4" PlexCore™ Decking
- 3/8" PlexCore™ Sidewall Liner
- 16" PlexCore™ Ramp Extension
- 3-Year Limited Warranty



Turbo Package with additional optional equipment available at additional cost.

*Trailers equipped with 7,000 lb. axles do not have Goodyear® tires as standard equipment.



GET MORE | GO FURTHER

www.haulmark.com

Specifications, features, options, packages & pricing subject to change **without** notice. See your authorized Haulmark® dealer for more information.