

## **SPECIFICATIONS**



			A STATE OF THE STA		
		EGP8520T3	EGP8524T3	EGP8528T4	EGP8532R4
Body:	Length Width	20' 0" 8' 4"	24' 0" 8' 4"	28' 0" 8' 4"	32' 0" 8' 4"
Overall:	Length Width Height (to top of roof vent)	24' 7" 8' 6" 9' 1"	28' 7" 8' 6" 9' 1"	32' 7" 8' 6" 9' 3"	36' 7" 8' 6" 9' 3"
Interior:	Length Width Height	19' 8" 8' 1" 6' 10"	23' 8" 8' 1" 6' 10"	27' 8" 8' 1" 6' 10"	31' 8" 8' 1" 6' 10"
Width Between Wheel Boxes		83"	83"	83"	83"
Height of Wheel Box from Floor		10"	10"	10"	10"
Platform Height at Beavertail		19"	19"	21"	21"
Torflex® Suspension E-Z Lube® Axles: Qty		Tandem	Tandem	Tandem	Triple
Electric Brakes with Breakaway Kit		Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Tire S Tire Load Ra		ST225/75R15 E	ST225/75R15 E	ST235/80R16 E	ST235/80R16 E
Hitch Ball Size		2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball		20"	20"	22"	22"
Hitch Weight (% of Curb Weight)		10% - 15%	10% - 15%	10% - 15%	10% - 15%
GVWR		9,900 lbs.	9,900 lbs.	12,000 lbs.	18,000 lbs.
Rear Ramp Door Opening - Width x Height		96" x 78"	96" x 78"	96" x 78"	96" x 78"
12v Male Connection		7-way	7-way	7-way	7-way
Tube Main Rails		2" x 6"	2" x 6"	2" x 8"	2" x 8"
Beavertail		48"	48"	72"	72"
	The second secon				

## **STANDARD FEATURES**

- Flat Front/Flat Roof Design
- Roof and Sidewall Structure
  - -16" OC Floor Crossmembers
  - -16" OC Tube Wall Posts
  - -16" OC Tube Roof Structure
- 54" A-Frame with Center Tube
- Adjustable Height 25/16" Wallace Forge Cast Coupler (Made in the USA)
- Square Tube 8K Dropleg Sidewide Jack with Footplate (Bolt-On/Replaceable)
- .040 White Aluminum Exterior, Smooth Bonded
- Cast Aluminum Corners (Front & Rear)
- Stainless Steel Cap and Front Corners
- Polished Aluminum Rear Corners & Header
- 1-Piece Aluminum Roof
- ArmorTech<sup>™</sup> on A-Frame and Rear End Rail
- 24" ATP Stoneguard
- Spring-Assisted Rear Ramp Door with 96"W Opening
- 16" PlexCore™ Ramp Extension
- Locking Paddle Latch on Rear Ramp Door
- 36" x 78" Side Entry Door with Recessed Step
- Spread Torflex® Axle Design with Drop Skirting
- Goodyear® Radial Tires with Black Viper Aluminum Wheels
- 12v Clear Lens LED Exterior Lighting
- 12v Clear Lens Slim Line Tail Light (2 pr.)
- 12v LED Dome Lights with Wall Switch (4)
- 14" x 14" Non-Powered Roof Vent (2)
- 5,000 lbs. Square D-Rings with Welded Plate (4)
- 3/4" PlexCore™ Decking
- 3/8" PlexCore™ Sidewall Liner
- · Economy Ceiling Liner
- 3-Year Limited Warranty





Turbo Package with additional optional equipment available at additional cost.



