

**GRIZZLY ALX — ALL ALUMINUM**

**Haulmark®**

## **THE BENCHMARK IN TOUGHNESS & LOW MAINTENANCE**

If you've got a job to do, the Haulmark® **GRIZZLY ALX** is the way to do it. All Aluminum construction delivers a lighter trailer for better fuel economy and increased hauling capacity. The Haulmark® **GRIZZLY ALX** won't rust even on the saltiest roads, so your trailer will keep looking great job after job, year after year. Beauty and brawn in one easy-to-tow, lightweight package!



*Trailer shown may feature optional equipment available at an additional charge.*

**GRIZZLY ALX**  
ALL ALUMINUM

# SPECIFICATIONS

**GRIZZLY ALX**  
ALL ALUMINUM

	GRALX714T2*	GRALX716T2*	GRALX8516T2*	GRALX8520T2*	GRALX8524T3
<b>Body:</b> Length (Including "V") Width	17'0" 7'0"	19'0" 7'0"	19'0" 8'4"	23'0" 8'4"	27'0" 8'4"
<b>Overall:</b> Length Width Height	19'1" 8'6" 8'4"	21'1" 8'6" 8'4"	21'1" 8'6" 8'6"	25'1" 8'6" 8'6"	29'1" 8'6" 8'7"
<b>Interior:</b> Length Width Height	16'7" 6'9" 6'6"	18'7" 6'9" 6'6"	18'7" 8'1" 6'6"	22'7" 8'1" 6'6"	26'7" 8'1" 6'6"
<b>Platform Height</b>	18"	18"	20"	20"	20"
<b>Axles:</b> Suspension Quantity Start Angle	Dexter® Torflex Tandem 10° Up	Dexter® Torflex Tandem 10° Up	Dexter® Torflex Tandem 10° Up	Dexter® Torflex Tandem 10° Up	Dexter® Torflex Tandem 10° Up
<b>Electric Brakes with Breakaway Kit</b>	4-Wheel Electric Drum	4-Wheel Electric Drum	4-Wheel Electric Drum	4-Wheel Electric Drum	4-Wheel Electric Drum
<b>Radial Tire Size Tire Load Range</b>	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST225/75R15 D
<b>Hitch Ball Size</b>	2½"	2½"	2½"	2½"	2½"
<b>Hitch Height to Top of Ball</b>	17" to 21"	17" to 21"	19" to 23"	19" to 23"	19" to 23"
<b>Hitch Weight (% of Curb Weight)</b>	10% - 15%	10% - 15%	10% - 15%	10% - 15%	10% - 15%
<b>GVWR</b>	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.	9,990 lbs.
<b>Curb Weight (Approximate)</b>	2,090 lbs.	2,360 lbs.	2,740 lbs.	3,220 lbs.	3,700 lbs.
<b>Payload Capacity (Approximate)</b>	4,910 lbs.	4,640 lbs.	4,260 lbs.	3,780 lbs.	6,290 lbs.
<b>Rear Door Opening - Width x Height</b>	78" x 74"	78" x 74"	94" x 74"	94" x 74"	94" x 74"
<b>Side Door Width</b>	36"	36"	36"	36"	36"
<b>Tube Main Rails</b>	2" x 4"	2" x 4"	2" x 6"	2" x 6"	2" x 6"
<b>12v Trailer Plug Connection</b>	7-Way	7-Way	7-Way	7-Way	7-Way

\*Available in 9,990 lb. GVWR

## STANDARD FEATURES

- DuraCage™ Aluminum Construction
  - Aluminum Tube Main Rails
  - 16" OC Floor Crossmembers (Full Height of Main Rail)
  - 16" OC Tube Vertical Posts
  - 16" OC Tube Roof Bows
  - Dust-Proof Sidewalls
- All-Aluminum Hardware
- Adjustable Height 2-5/16" Wallace Forge® Cast Coupler
- 8,000 lb. Dropleg Sidewind Jack with Footplate
- Dexter® Torflex Axles with EZ-Lube® Hubs
- Radial Tires with Silver Viper Aluminum Wheels
- 3/4" PlexCore™ High-Performance Floor & Ramp Decking
- 3/8" PlexCore™ High-Performance Interior Sidewall Liner
- 5,000 lbs. D-Rings (4)
- Sidewall Vents
- 12v High Output LED Dome Lights with Switch (800 Lumens)
- .080 ACP Panels (Select Colors)
- Thick, Bold Extruded Aluminum Top/Bottom Trim
- 1-Piece Aluminum Roof
- Smooth Aluminum Fenderettes
- 24" ATP Stoneguard
- Heavy-Duty 36"W Side Door with Flush Lock & Dead Bolt (1½" Core)
- Medium Duty Rear Ramp Door w/ Ramp Extension
- 12v Smoked Lens LED Slim Line Tail Lights
- 12v Smoked Lens LED Clearance Lights
- Rear ID Bar with Built-In Loading Light with Switch
- 3-Year Limited Warranty



Shown with optional rear ramp door available at additional charge



Silver Viper Aluminum Wheels & Heavy-Duty Side Door Standard



Specifications, features, options, packages & pricing subject to change **without** notice. Contact your authorized Haulmark® dealer for more information.