

SPECIFICATION PP8516T2 Length Width 17' 10' Body: 8'4" 19' 6" Length



PP8524T2

25' 10"

8' 4"

27' 6"

PP8520T2 21' 10"

8' 4"

23'6"

Overall: Width Height	8' 6" 8' 5"	8' 6" 8' 5"	8' 6" 8' 5"
Length Interior: Width Height	17' 6" 8' 0" 6' 6"	21' 6" 8' 0" 6' 6"	25' 6" 8' 0" 6' 6"
Width Between Wheel Wells	83.5"	83.5"	83.5"
Platform Height	19"	19"	19"
Spring Suspension E-Z Lube® Axles: Qty Total Axle Capacity	Tandem 7,000 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.
Electric Brakes with Breakaway Kit	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size Tire Load Range	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C
Hitch Ball Size	2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball	20"	20"	20"
Hitch Weight (% of Curb Weight)	10% to 15%	10% to 15%	10% to 15%
Curb Weight (Approximate)	2,800 lbs.	3,100 lbs.	3,500 lbs.
GVWR	7,000 lbs.	7,000 lbs.	7,000 lbs.
Payload Capacity (Approximate)	4,200 lbs.	3,900 lbs.	3,500 lbs.
Rear Ramp Door Opening - Width x Height	91″ x 75″	91" x 75"	91" x 75"
12v Male Connection	7-way	7-way	7-way
	for the		

STANDARD FEATURES

- · V-Nose Profile
- 15" Radial Tires with Silver Mod Wheels
- Smooth Aluminum Fenderettes
- White .024 Aluminum Exterior (with screws)
- 1-Piece Aluminum Roof
- 12v LED Exterior Lighting
- 12v LED Slim Line Tail Lights
- 16" Starbright Stoneguard
- Flow-Thru Sidewall Vents
- Rear Ramp Door with Spring Assist
- 32" Side Door with Bar Lock
- 12v LED Dome Light
- 3/4" PlexCore[™] Decking
- 500 lb. D-Ring Tie-Downs (4)
- Economy Sidewall Liner
- Spring Axles with 4" Drop
- E-Z Lube[®] Hubs
- Electric Brakes with Breakaway Kit
- 2" x 6" Tube Main Rails
- · Entire Chassis Undercoated
- 16" OC Vertical Posts
- 24" OC Crossmembers
- 24" OC Tube Roof Bows
- 1-Year Limited Warranty





Trailers shown may feature optional equipment available at an additional charge.



