

Haulmark®

ENHANCED VALUE

**THERE'S A WIDE-WORLD
OUT THERE. EXPERIENCE
IT ALL!**

In life, there are no shortcuts to success, and you never settle for second best. Fueled by relentless innovation, the Transport® V-Nose is a value-packed combination of performance, durability, and low-maintenance. Our trailers defy the routine and are designed to dominate every type of cargo hauling activity. At Haulmark®, we build trailers that work (and play) as hard as you do.



Trailers shown may feature optional equipment available at an additional charge.

TRANSPORT®

SPECIFICATIONS

TRANSPORT

	TSV58S2	TSV610S2	TSV612S2	TSV612T2	TSV712T2	TSV714T2	TSV716T2
Body: Length Width	9' 5" 5' 0"	11' 7" 6' 0"	13' 7" 6' 0"	13' 7" 6' 0"	13' 7" 7' 0"	15' 7" 7' 0"	17' 7" 7' 0"
Overall: Length Width Height	11' 6" 6' 8" 7' 2"	14' 0" 7' 8" 8' 2"	16' 0" 7' 8" 8' 2"	16' 0" 7' 8" 8' 3"	15' 8" 8' 6" 8' 3"	17' 8" 8' 6" 8' 3"	19' 8" 8' 6" 8' 3"
Interior: Length Width Height	9' 1" 4' 8" 5' 6"	11' 3" 5' 8" 6' 6"	13' 3" 5' 8" 6' 6"	13' 3" 5' 8" 6' 6"	13' 3" 6' 8" 6' 6"	15' 3" 6' 8" 6' 6"	17' 3" 6' 8" 6' 6"
Platform Height	18"	18"	18"	19"	19"	19"	19"
Spring Suspension E-Z Lube® Axles: Qty Total Axle Capacity	Single 3,500 lbs.	Single 3,500 lbs.	Single 3,500 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.
Electric Brakes with Breakaway Kit	N/A	Optional	Optional	Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size Tire Load Range	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C
Hitch Ball Size	2"	2"	2"	2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball	16"	16"	16"	17"	17"	17"	17"
Hitch Weight (% of Curb Weight)	10% to 15%	10% to 15%	10% to 15%	10% to 15%	10% to 15%	10% to 15%	10% to 15%
Curb Weight (Approximate)	935 lbs.	1,195 lbs.	1,325 lbs.	1,740 lbs.	2,000 lbs.	2,125 lbs.	2,300 lbs.
GVWR	2,980 lbs.	2,980 lbs.	2,980 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.
Payload Capacity (Approximate)	2,045 lbs.	1,785 lbs.	1,655 lbs.	5,260 lbs.	5,000 lbs.	4,875 lbs.	4,700 lbs.
Rear Door Opening - Width x Height	51" x 61"	63" x 67"	63" x 67"	63" x 67"	75" x 73"	75" x 73"	75" x 73"
Pass-Thru Door Opening - Width x Height	N/A	32" x 66"	32" x 66"	36" x 72"	36" x 72"	36" x 72"	36" x 72"
Cargo Control	500 lb. Wall Rope Rings	5,000 lb. D-Rings	5,000 lb. D-Rings	5,000 lb. D-Rings	5,000 lb. D-Rings	5,000 lb. D-Rings	5,000 lb. D-Rings
12v Male Connection	4-way	4-way	4-way	7-way	7-way	7-way	7-way

STANDARD FEATURES

- V-Front/Flat Roof Profile
- Spring Axles with E-Z Lube® Hubs
- Electric Brakes with Breakaway Kit *(Tandem Axle Models Only)*
- Silver Mod Wheels with 15" Radial Tires
- Smooth Aluminum Radius Fenders
- 24" ATP Stoneguard
- .030 Aluminum Exterior Bonded *(No Screws)*
- 1-Piece Aluminum Roof
- 12v LED Slim Line Tail Lights
- 12v LED Mini Clearance Lights
- Flow-Thru Sidewall Vents
- Rear Ramp Door with Spring Assist *(Single Swing Door on 5x8 Model)*
- PlexCore™ Ramp Extension *(Excludes 5x8 Model)*
- 36" Side Entry Door with Flush Lock *(No Side Door on 5x8 Model)*
- 12v LED Dome Lights with Wall Switch
- 3/4" PlexCore™ Flooring
- 3/8" PlexCore™ Sidewall Liner
- Entire Chassis Undercoated
- ArmorTech™ on A-Frame and Rear End Rail
- 2" X 4" Tube Main Rails *(2" X 3" on Single Axle Models)*
- 16" OC Tube Vertical Posts
- 16" OC Crossmembers
- 16" OC Tube Roof Bows
- 3-Year Limited Warranty



Trailers shown may feature optional equipment available at an additional charge.



GET MORE | GO FURTHER

www.haulmark.com

Specifications, features, options, packages & pricing subject to change **without** notice. See your authorized Haulmark® dealer for more information.