

Haulmark®

ENHANCED VALUE

GET THE JOB DONE RIGHT!

You work hard and you believe in doing the job, any job, the right way. From moving your friends into their new home to storing your favorite off-road vehicle or carefully transporting your family's antique heirlooms, you need a smart cargo trailer to help with all your hauling needs. At Haulmark®, we build trailers that work as hard as you do.



Trailers shown may feature optional equipment available at an additional charge.

TRANSPORT®

SPECIFICATIONS



	TS58S2	TS610S2	TS612S2	TS612T2	TS712T2	TS714T2	TS716T2
Body: Length Width	8' 9" 5' 0"	10' 9" 6' 0"	12' 9" 6' 0"	12' 9" 6' 0"	12' 9" 7' 0"	14' 9" 7' 0"	16' 9" 7' 0"
Overall: Length Width Height	11' 6" 6' 8" 7' 4"	14' 0" 7' 8" 8' 3"	16' 0" 7' 8" 8' 3"	16' 0" 7' 8" 8' 4"	15' 8" 8' 6" 8' 5"	17' 8" 8' 6" 8' 5"	19' 8" 8' 6" 8' 5"
Interior: Length Width Height	8' 5" 4' 8" 5' 6"	10' 5" 5' 8" 6' 6"	12' 5" 5' 8" 6' 6"	12' 5" 5' 8" 6' 6"	12' 5" 6' 8" 6' 6"	14' 5" 6' 8" 6' 6"	16' 5" 6' 8" 6' 6"
Platform Height	18"	18"	18"	19"	19"	19"	19"
Spring Suspension E-Z Lube® Axles: Qty Total Axle Capacity	Single 3,500 lbs.	Single 3,500 lbs.	Single 3,500 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.
Electric Brakes with Breakaway Kit	N/A	N/A	N/A	Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size Tire Load Range	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C
Hitch Ball Size	2"	2"	2"	2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball	16"	16"	16"	17"	17"	17"	17"
Hitch Weight (% of Curb Weight)	10% to 15%	10% to 15%	10% to 15%	10% to 15%	10% to 15%	10% to 15%	10% to 15%
Curb Weight (Approximate)	880 lbs.	1,100 lbs.	1,250 lbs.	1,650 lbs.	1,935 lbs.	2,100 lbs.	2,265 lbs.
GVWR	2,980 lbs.	2,980 lbs.	2,980 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.
Payload Capacity (Approximate)	2,100 lbs.	1,880 lbs.	1,730 lbs.	5,350 lbs.	5,065 lbs.	4,900 lbs.	4,735 lbs.
Rear Door Opening - Width x Height	51" x 61"	63" x 73"	63" x 73"	63" x 73"	75" x 73"	75" x 73"	75" x 73"
Pass-Thru Door Opening - Width x Height	N/A	32" x 66"	32" x 66"	36" x 66"	36" x 66"	36" x 66"	36" x 66"
Cargo Control	500 lb. Wall Rope Rings	5,000 lb. D-Rings	5,000 lb. D-Rings	5,000 lb. D-Rings	5,000 lb. D-Rings	5,000 lb. D-Rings	5,000 lb. D-Rings
12v Male Connection	4-way	4-way	4-way	7-way	7-way	7-way	7-way

STANDARD FEATURES

- Radius Front/Round Roof with TPO Front Cap
- Silver Mod Wheels with 15" Radial Tires
- Smooth Aluminum Radius Fenders *(Teardrop on 7' Wide Models)*
- .030 Aluminum Exterior Bonded *(No Screws)*
- .080 Aluminum Top Wrap
- 1-Piece Aluminum Roof
- 12v LED Slim Line Tail Lights
- 12v LED Mini Clearance Lights
- 24" ATP Stoneguard
- Flow-Thru Sidewall Vents
- Rear Ramp Door with Spring Assist *(Single Swing Door on 5x8 Model)*
- PlexCore™ Ramp Extension *(Excludes 5x8 Model)*
- 36" Side Entry Door with Flush Lock *(No Side Door on 5x8 Model)*
- 12v LED Dome Light with Wall Switch
- 3/4" PlexCore™ Decking
- 3/8" PlexCore™ Sidewall Liner
- Spring Axles with E-Z Lube® Hubs
- Electric Brakes with Breakaway Kit *(Tandem Axle Models Only)*
- 2" X 4" Tube Main Rails *(2" X 3" on Single Axle Models)*
- Entire Chassis Undercoated
- ArmorTech™ on A-Frame and Rear End Rail
- 16" OC Tube Vertical Posts
- 16" OC Crossmembers
- 16" OC Hat Section Roof Bows
- 3-Year Limited Warranty



Trailers shown may feature optional equipment available at an additional charge.



GET MORE | GO FURTHER

www.haulmark.com

Specifications, features, options, packages & pricing subject to change **without** notice. See your authorized Haulmark® dealer for more information.